





# SA15m Series Instant Hot Shower

With 10mA Extra-Safe RCCB Technology





### **INTERNAL PARTS**

1 Year Warranty On Internal Parts



#### SERVICE ASSURED

- After-Sales Service Assured
- Door To Door
- Spare Parts Available

## **CHROME SLIM** SLIDER BAR SET



Slim and unique slider bar. Just press to set the hand \*shower to your ideal position.

Chrome accessories are only available for silver colour.

# SPRAY OPTIONS

3 ideal shower mode spray pattern can be selected just by turning the spray selector, it's so easy!



Wide Spray



Maxi Spray



Jet Spray

### **INNOVATIVE AND SAFETY FEATURES**



**Built-In Double Pole RCCB System** 

- 10mA Sensitivity
- Test / Reset Safety Functions
   Reliable Electro-mechanical **Functions**



**Electronic Power Control** 

- Stepless Electronic Power
- Ideal Shower Temperature
- Energy Saving



**Innovative SF Valve** 

- 1/4 Turn Ceramic Valve
- Stop And Control
- Water Volume Built-In Filter
- Water Saving



Safety Thermostat / Thermal Cut-Out

- Anti Scalding
- Overheating Protection
- Prevents Fire Hazard



**Splash Proof Casing IP25** 

- Against Water Splash
- Against Access To
- Hazardous Parts
- Safety Certified

# SA15m **SPECIFICATION**

Electrial Loading 3.3 kW 15Amps. 230V a.c 50Hz Min. Water Pressure 10kPa/ 1.45psi/ 0.1bar Max. Water Pressure 380kPa/ 55psi/ 3.8bar Min. Water Flow 2 Litres per Minute Max. Water Flow 8 Litres per Minute Water Temp. Control Water Connection 45 plash Proof Protection IP25 Double Pole ELCB 10mA Trip Sensitivity Dimensions 221mm x 341mm x 89mm Weight 2.5Kg		
Max. Water Pressure  380kPa/ 55psi/ 3.8bar  Min. Water Flow  2 Litres per Minute  Max. Water Flow  8 Litres per Minute  Water Temp. Control  Water Connection  4015mm (½" BSP), Single Point System  ABS Casing  Splash Proof Protection IP25  Double Pole ELCB  Dimensions  221mm x 341mm x 89mm	Electrial Loading	3.3 kW 15Amps. 230V a.c 50Hz
Min. Water Flow  Max. Water Flow  Water Temp. Control  Water Connection  ABS Casing  Double Pole ELCB  Dimensions  2 Litres per Minute  8 Litres per Minute  9 Litres per Minute	Min. Water Pressure	10kPa/ 1.45psi/ 0.1bar
Max. Water Flow 8 Litres per Minute Water Temp. Control Water Connection ABS Casing Double Pole ELCB Dimensions  8 Litres per Minute 8 Litres per Minute 915mm (½" BSP), Single Point System 915mm (½" BSP), Singl	Max. Water Pressure	380kPa/ 55psi/ 3.8bar
Water Temp. Control Water Connection ABS Casing Double Pole ELCB Dimensions Stepless Power Control  ### ### ### ### ### ### ### ### ### #	Min. Water Flow	2 Litres per Minute
Water Connection ø15mm (½" BSP), Single Point System ABS Casing Splash Proof Protection IP25 Double Pole ELCB 10mA Trip Sensitivity Dimensions 221mm x 341mm x 89mm	Max. Water Flow	8 Litres per Minute
ABS Casing Splash Proof Protection IP25  Double Pole ELCB 10mA Trip Sensitivity  Dimensions 221mm x 341mm x 89mm	Water Temp. Control	Stepless Power Control
Double Pole ELCB 10mA Trip Sensitivity  Dimensions 221mm x 341mm x 89mm	Water Connection	ø15mm (1/2" BSP), Single Point System
Dimensions 221mm x 341mm x 89mm	ABS Casing	Splash Proof Protection IP25
	Double Pole ELCB	10mA Trip Sensitivity
Weight 2.5Kg	Dimensions	221mm x 341mm x 89mm
	Weight	2.5Kg



















### Authorised Dealer:

Manufactured by: JOVEN ELECTRIC CO.

JOVEN ELECTRIC (S) PTE LTD UEN No.199500898Z No.10 Ubi Crescent, #02-18 Ubi Techpark, Singapore 408564 Tel: +65 6283 3181 / +65 6749 6421 | Fax: +65 6749 3575 Email: sales@jovenelectric.com | www.jovenelectric.com